O-Addensante

THICKENING AGENT

TECHNICAL DATA SHEET n. INT/ad/00

www.oikos-group.it/addensanteoikos

Technical Characteristics

ADDENSANTE OIKOS is a special additive that can be used, when a product that is to be applied is too liquid for application, to bring the viscosity of the product to a level suitable for its use. The product can be used for the range of OIKOS products formulated using lime putty and for all thick, acrylic coatings. It is easy to use and has an immediate effect. ADDENSANTE OIKOS is composed of highly efficient rheological additives in water dispersion. It is a product with a Low Environmental Impact, friendly to both humans and the environment.

Ideal Use

ADDENSANTE OIKOS can be used with lime based products:

- TRAVERTINO ROMANO
- MARMORINO NATURALE
- FINITURA AUTOLUCIDANTE
- RAFFAELLO DECOR STUCCO
- RAFFAELLO MADREPERLATO
- COCCIO ANTICO
- COCCIO CEMENTO
- RASATURA ALLA CALCE

And for the thick coatings:

- ELASTRONG VENEZIA/VENEZIA FINE
- DECORSIL BOLOGNA/ FINE
- DECORSIL VENEZIA
- COLOR FINISH

The product

Composition	Acrylic Copolymers in water dispersion.
Specific weight	1,1 Kg/l ±3%
рН	2÷4
Storage temperature	+2°C÷+36°C. Keep from Freezing
Packaging	Tube of 50 ml

L'applicazione

Dilution/Mix	1 pot (50 ml): Travertino Romano, Coccio Antico, Coccio Cemento 1-2 pots (50-100 ml): Marmorino Naturale, Finitura Autolucidante, Raffaello Decor Stucco, Raffaello Madreperlato, Rasatura alla Calce 1-3 pots (50-150 ml): Elastrong Venezia/Venezia Fine, Decorsil Bologna/Bologna Fine, Decorsil Venezia, Color Finish
Application tool	Drill whisk
Tools cleaning	Water

Application Method

A few minutes before application, slowly add AD-DENSANTE directly into the product to be thickened mixing the product using a drill whisk, until the desired density is obtained.

The effect of the additive will be immediately evident.

Recommended dosage per bucket (14L/20 Kg)

- 1 pot (50 ml): Travertino Romano, Coccio Antico, Coccio Cemento:
- 1-2 pots (50-100 ml): Marmorino Naturale, Finitura Autolucidante, Raffaello Decor Stucco, Raffaello Madreperlato, Rasatura alla Calce
- 1-3 pots(50-150 ml): Elastrong Venezia/Venezia Fine, Decorsil Bologna/Bologna Fine, Decorsil Venezia, Color Finish

For smaller buckets of product, use ADDEN-SANTE according to the desired viscosity.

Safety information

The product is free of heavy metals such as lead or chrome. It does not contain toxic solvents, aromatics or chlorides. There is no risk of any dangerous polymerisation. The product is considered to be a non-dangerous substance if used in the technically correct manner. Normal cautionary measures for the handling of water based paints are advised. No special arrangements are required for the storage, movement and transportation of the product; the containers, residue, eventual spilt material should be cleaned up using absorbent inert material such as sand, soil etc. etc. and then disposed of in accordance with the regional and national regulations in force at that time. Transportation must be carried out in accordance with international

