

Cera per Stucco

**PROTECT
POLISH**

**TECHNICAL
DATA SHEET
n. INT/cs/00**

www.oikos-group.it/cerastucco

Technical characteristics

CERA per STUCCO is decorative wax in paste form, created to exalt the shine of stucco. Thanks to its quick and simple, one coat, trowel application, it is possible to obtain excellent marble effects whilst still respecting the technique and the natural feel of the stucco finish on which the Cera per Stucco is applied. The additives in the product facilitate its application and make it easier to polish. Cera per Stucco protects the surface on to which it is applied making it rub resistant. It has low odour, is non inflammable and is friendly to both humans and the environment.

Ideal use

Polishing and protection of interior walls and furnishings coated with decorative stucco.

Surface preparation

Wait atleast 6-8 hours after the application of the last coat of stucco and in any case until it is completely dry.

Application method

Apply a single, even coat of CERA per STUCCO using a float (inox steel trowel). To further enhance the shine, after 24 hours it is possible to polish the surface using a soft cloth.

The product

Composition	Based on special waxes and water
Specific weight	0.97 kg/l \pm 3%
Viscosity	Paste
Storage temperature	+5C \div +36°C. Keep from freezing
Reaction to fire	Negative if applied on a non inflammable base; water based material with dry thickness of less than 0,600mm
Emission limits of Volatile Organic Compounds (VOC), in accordance with the norm 2004/42/CE	<ul style="list-style-type: none">• Classification: A/I• VOC: 70g/l (max)• Limit phase I(from 1.1.2007): 300g/l• Limit phase II (from 1.1.2010): 200g/l
Colours	Transparent, colourless
Packaging	1 Litre

The application

Dilution	Ready to use
Yield	80/100m ² /l
Application tools	Inox steel trowel by OIKOS
Base	Decorative, lime based stucco
Application temperature	+5°C \div +36°C (with relative humidity not exceeding 80%)
Drying time until touch dry	1 h (temperature = 20°C with relative humidity at 75%)
Total drying time	20 \div 24 days (temperature = 20°C with relative humidity at 75%)
Tools cleaning	Water

Safety information

The product is free of heavy metals such as lead or chrome. It does not contain toxic solvents, aromatics or chlorides. There is no risk of any dangerous polymerisation. The product is considered to be a non-dangerous substance if used in the technically correct manner. Normal cautionary measures for the handling of water based paints are advised. No special arrangements are required

for the storage, movement and transportation of the product; the containers, residue, eventual spilt material should be cleaned up using absorbent inert material such as sand, soil etc. etc. and then disposed of in accordance with the regional and national regulations in force at that time. Transportation must be carried out in accordance with international agreements.