



## DECORATIVE PAINT GOLDEN EFFECT

## TECHNICAL DATA SHEET n. INT/do/04

www.oikos-group.it/nevada

### Technical Qualities

NEVADA la Pintura Dorada is a decorative paint that unifies colours, contrasts and golden shimmers and brings to the wall an enchanting appearance. Thousands of tiny drops of paint that are broken by the passing of a trowel and that due to a particular magnetism, become a blend of colours with a golden touch. Thanks to its formulation and the special pigments used, it is possible to admire the numerous shades of colour that are able to bring new sensations to walls, from a golden amber to beautiful golden shimmers that give precious reflections to an ambiance. NEVADA la Pintura Dorada is washable, waterproof, scratch proof and helps to prevent the formation of mould. It is particularly indicated for the decoration of surfaces in prestigious environments such as villas, palaces, offices, high class studios, apartments and elegant boutiques and shops. Easy to apply, NEVADA allows application without leaving joints or imperfections. The product has a low odour level, is non inflammable and is friendly both to humans and the environment

### Ideal Use

Interior surfaces in every type of building both historic and modern.

### Surface Preparation

New surfaces should be dry and thoroughly mature. On old surfaces or previously painted surfaces, remove deposits of dust, smog or other impurities by brushing or washing. Remove any loose or crumbling material. Follow this by applying, if necessary, a coat of the special sealer NEOFIX by OIKOS. Wait 4 ÷ 6 hours until dry. Apply one or two coats of FONDO MURALES by OIKOS as a base coat. Wait 6 ÷ 8 hours until dry.

### Application Method

Apply Nevada la Pintura Dorada by the special Spanish Brush by OIKOS crossing the brush strokes, immediately pass over the same part of the surface with the Spanish Brush empty, in order to evenly distribute the product over the surface. After 5 ÷ 10 minutes pass over the surface again with an inox steel trowel by OIKOS, applying light pressure to squash the product but without removing it.

### Finish and Protective

To protect better NEVADA from wear and aging, apply the special transparent, protective varnish WATINS LUX or IGROLUX by OIKOS. To achieve a finish with brilliant reflections, it is possible to mix with WATINS LUX or IGROLUX the additive DECORGLITTER by Oikos.

### The product

|   |  |
|---|--|
| Composition   | acrylic resins in water dispersion, organic and inorganic pigments with golden effect  |
| Specific weight   | 1,00 kg/l ±3%  |
| pH  | 6 ÷ 7  |
| Viscosity   | 7.500 ÷ 11.500 CPS Brookfield (RVT 20 revs/min. a 25°C)  |
| Storage temperature   | +2°C ÷ +36°C. (Keep from freezing)   |
| Reaction to fire  | Negative if the product is applied on a non inflammable base; water based material with dry thickness of less than 0,600mm.  |
| Resistance to washing   | Washable according to the norm UNI 10560: 1996   |
| Emission limits of Volatile Organic Compounds (VOC) according to directive 2004/42/CE | <ul style="list-style-type: none"> <li>• Classification: A/k</li> <li>• VOC: 10g/l (max)</li> <li>• Limit Phase I (from 1.1.2007), 150g/l</li> <li>• Limit Phase II (from 1.1.2010): 100g/l</li> </ul> |
| Colours   | shades of the colour chart   |
| Packaging   | Liters 1 – 4   |

### The application

|                         |  |
|-------------------------|--|
| Dilution                | 5 ÷ 10% with drinkable water   |
| Yield                   | 6-8 m <sup>2</sup> /l according to surface absorption and the desired effect |
| Application tools       | Spanish-Brush and inox steel trowel by OIKOS                                 |
| Fixative                | NEOFIX by OIKOS  |
| Base coat               | FONDO MURALES by OIKOS   |
| Application temperature | +5°C ÷ +36°C (with relative humidity not exceeding 80%)                      |
| Drying time Touch dry   | 3 ÷ 4 hour (temperature = 20°C with relative humidity around 75%)            |
| Drying time fully cured | 2 ÷ 3 days (temperature = 20°C with relative humidity around 75%)            |
| Tools cleaning          | Water  |
| Warning                 | Mix manually or in a gyroscopic mixer for max 1 min. at low speed            |

### Safety information

The product is free of heavy metals such as lead or chrome. It does not contain toxic solvents, aromatics or chlorides. There is no risk of any dangerous polymerisation. The product is considered to be a non dangerous substance if used in the technically correct manner. Normal cautionary measures for the handling of water based paints are advised. No special arrangements are required for the storage, movement and transportation of the product; the containers, residue, eventual spilt material should be cleaned up using absorbent inert material such as sand, soil etc. etc. and then disposed of in accordance with the regional and national regulations in force at that time. Transportation must be carried out in accordance with international agreements.

### Specifications

New surfaces should be dry and thoroughly mature. On old surfaces or previously painted surfaces, remove deposits of dust, smog or other impurities by brushing or washing. Remove any loose or crumbling material. Follow this by applying, if necessary, a coat of the special sealer NEOFIX by OIKOS. Wait 4 ÷ 6 hours until dry. Apply one or two coats of FONDO MURALES by OIKOS as a base coat. Wait 6 ÷ 8 hours until dry. Apply Nevada la Pintura Dorada by the special Spanish Brush by OIKOS crossing the brush strokes, immediately pass over the same part of the surface with the Spanish Brush empty, in order to evenly distribute the product over the surface. After 5 ÷ 10 minutes pass over the surface again with an inox steel trowel by OIKOS, applying light pressure to squash the product but without removing it. All must be carried out in accordance with the norms of application, at a cost of ..... m<sup>2</sup>. inclusive of materials and labour.

The company Oikos S.r.l guarantees, to the best of its own technical and scientific knowledge, that the information contained in this technical data sheet is correct. Notwithstanding that indicated above, Oikos takes no responsibility for the results obtained through the use of this product in as much as it is not possible for Oikos to check or control the application method used. For this reason, we recommend that you check carefully that each product chosen, is suitable for each individual use to which it is put.

